

QUICKCABLE

Material Safety Data Sheet (MSDS)

Description: Cleaner Spray

Part Number: 120131

SECTION I CONTACT INFORMATION

Date: July 2009
Quick Cable Corporation
3700 Quick Cable Drive, Franksville, WI 53126
Telephone: 1-800-558-8667

Emergency Telephone: INFOTRAC 1-800-535-5053

Quick Cable Product I.D.: 120131

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components Specific Chemical Identity (Common Name(s))	CAS#	OSHA PEL	AGGIH TLV	Percent
Sodium Bicarbonate	#144-55-8	N/A	N/A	<10.0
Water		N/A	N/A	>90.0
Propellant: Isobutane	#75-28-5	N/A	N/N	<10.0
or Butane	#106-97-8	800 ppm	800 ppm	<10.0
or Propane	#74-98-6	1000 ppm	2500 ppm	<10.0
Detergents	Mixture	N/A	N/A	<10.0
2-Butoxy Ethanol	#111-76-2	25 ppm	25 ppm	<10.0

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Chemicals without Propellant/ Propellent

Appearance and odor: A quick breaking foam

Solubility in Water: Soluble in Water

Freezing Point: 32°F/ Not determined

Boiling Point: 212°F

Evaporation Rate: Not Determined

Specific Gravity (H₂O=1): 1.04/ .095

Vapor Density (AIR=1): Not determined

Vapor Pressure (mm Hg): Not Determined

% Volatile: 3.0% / 97%

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): Propellant Below 20°F

Extinguishing Media: Carbon Dioxide, Foam

Unusual Fire and Explosion Hazards: Do not spray near open flame. Flammable material. Aerosol cans may explode.

Special Fire Fighting Procedures: Remove Aerosol containers from fire area if possible.

Flammable Limits: Propellant

LEL: 1.9 **UEL:** 9.5

SECTION V REACTIVITY DATA

Stability: Stable

Conditions to avoid: Do not store above 120°F to prevent cans from exploding.

Hazardous Decomposition of By-products: Carbon monoxide, carbon dioxide

Materials to avoid: NA

SECTION VI HEALTH HAZARD DATA

Primary Route(s) of Entry: Inhalation, skin and ingestion

Signs and Symptoms of Exposure: *Inhalation:* Over-exposure may result in light-headedness, staggering gait, giddiness, and possible nausea. *Skin and Eyes:* May cause irritation. *Ingestion:* Harmful or fatal if swallowed.

Chronic overexposure: Reports have associated repeated and prolong overexposure to solvents with permanent brain and nervous system damage.

Medical Conditions Generally Aggravated by Exposure: None identified

Emergency and First Aid Procedures: (If symptoms persist, contact a physician)

Inhalation: Remove to fresh air, Give artificial respiration if needed.

Ingestion: Induce vomiting on the advice of a physician.

Eyes: Flush with water for 15 minutes.

Skin: Remove contaminated clothing and wash with soap and water.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Steps taken in Case Material is Released or Spilled: Remove all sources of ignition, ventilate, and avoid breathing vapors above exposure limits.

Waste disposal Method: Dispose of in accordance with local, state or federal regulations.

Precautions to be taken in Handling and Storing: Do not store above 120°F. Keep away from children. Do not puncture or incinerate. Do not spray near fire or open flame.

SECTION VIII CONTROL MEASURES

Respiratory Protection (Specific Type): Use NIOSH/MSHA compliant respirators or a self contained breathing apparatus above exposure limits.

Ventilation: Adequate to prevent accumulation of vapors.

Protective Clothing: Wear chemically protective gloves and safety glasses. Use splash aprons and boots if splashing occurs.

Eye and Face Protection: Safety glasses, face shield if splashing occurs.

Other Protective Equipment: Not needed

SECTION IX OTHER REGULATORY INFORMATION

	NFPA	HMIS
Health (Blue)	1	1
Flammability (Red)	4	4
Reactivity (Yellow)	0	0

SARA Title III: Section 311/312: Acute **Section 313:** Butoxy Ethanol

Extremely Hazardous Substance: No

This information is accurate to the best of Quick Cable Corporation's knowledge or obtained from sources believed by Quick Cable to be accurate. Before using this product, read all warnings and directions on the label.