

QUICKCABLE

Material Safety Data Sheet (MSDS)

Description: Protective Spray

Part Number: 120141

SECTION I CONTACT INFORMATION

Date: July 2009
Quick Cable Corporation
3700 Quick Drive, Franksville, WI 53126
Telephone: 1-800-558-8667

Emergency Telephone: INFOTRAC 1-800-535-5053

Quick Cable Product I.D.: 120141

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components Specific Chemical Identity (Common Name(s))	CAS#	ACGIH TLV	OSHA PEL	Range Percent By Weight	Average
Inhibited Paraffinic Oil	Mixture 5m	5 mg/m3	5 mg/m3	(mist)	10-20%
Microcrystalline Wax	8009-03-8	NE	5 mg/m3	NE	15-35%
Xylene	1330-20-7	100 ppm	100 ppm	NE	1-10%
Petroleum Distillate	6474-28-87	NE	400 ppm	100 ppm	10-20%
Isohexanes	107-83-5	500 ppm	500 ppm	NE	30-50%
n-Hexane	110-54-3	50 ppm	50 ppm		1-10%
Heptane	142-82-5	400 ppm	40 ppm	NE	1-10%

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and odor: Red viscous liquid.
Solubility in Water: Negligible in Water
Freezing Point: Not Determined
Boiling Point: 138°F-144°F
Evaporation Rate: Not Determined

Specific Gravity (H₂O=1): 0.75
Vapor Density (Air=1): >Air
Vapor Pressure (mm Hg): Not Determined
% Volatile: 70.0% lbs./gal 4.47

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): <0°F (TCC) Flammable

Extinguishing Media: Carbon Dioxide, Foam, and Dry Chemical

LEL: 1.7 **UEL:** 9.0

Hazardous Combustion Products: Thermal-carbon monoxide

Unusual Fire and Explosion Hazards: Do not spray near open flame. Flammable material.

Special Fire Fighting Procedures: Remove Aerosol containers from fire area if possible. Use a self-contained breathing apparatus for fire fighting. Aerosol cans may explode if heated above 120°F.

DANGER: Extremely Flammable

SECTION V REACTIVITY DATA

Stability: Stable

Chemical Incompatibilities: Strong oxidizers

Conditions to avoid: Do not store above 120°F to prevent cans from exploding. **Hazardous Polymerization:** No

Hazardous Decomposition of By-products: Thermal-carbon monoxide

Materials to avoid: Strong oxidizers

SECTION VI HEALTH HAZARD DATA

Primary Route(s) of Entry: Inhalation, skin. Harmful or fatal if swallowed
Signs and Symptoms of Exposure: *Inhalation:* Headaches, dizziness, nausea and anesthesia. *Skin and Eyes:* May cause irritation/drying. *Ingestion:* NA.
Chronic overexposure: Dermatitis
Medical Conditions Generally Aggravated by Exposure: None identified
Emergency and First Aid Procedures: (If symptoms persist, contact a physician)
Inhalation: Remove to fresh air, Give artificial respiration if needed
Ingestion: Do not induce vomiting. Call a physician
Eyes: Flush with large amounts water for 15 minutes
Skin: Remove contaminated clothing and wash area with soap and water

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Steps taken in Case Material is Released or Spilled: Ventilate areas. Absorb with inert material and place in a closed container.
Waste disposal Method: All used and unused product should be disposed of in conformance with local, state, and federal regulations. This material may be considered a hazardous waste under U.S.E.P.A. RCRA regulations.
Precautions to be taken in Handling and Storing: Store in a cool, dry area away from heat. EXTREMELY FLAMMABLE.
Other Precautions: Do not puncture or incinerate aerosol cans. Do not spray near fire or open flames.

SECTION VIII CONTROL MEASURES

Respiratory Protection (Specific Type): Use NIOSH/MSHA compliant respirators or a self contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.
Ventilation: Adequate to prevent accumulation of vapors and maintain levels below exposure limits.
Protective Clothing: Wear chemically protective gloves and safety glasses. Use splash aprons and boots if splashing occurs.
Eye and Face Protection: Safety glasses, face shield if splashing occurs.
Work Hygienic Practices: Good personal hygiene and work practices are recommended.

SECTION IX OTHER REGULATORY INFORMATION

	NFPA	HMIS
Health (Blue)	3	2
Flammability (Red)	4	4
Reactivity (Yellow)	2	0

PPE: B
SARA Title III: Section 311/312: Acute **Section 313:** n-Hexane, Xylene
Extremely Hazardous Substance: No
California Prop 65: This product contains chemicals known to the state of California to cause cancer, birth defects and otreproductive harm.

This information is accurate to the best of Quick Cable Corporation's knowledge or obtained from sources believed by Quick Cable to be accurate. Before using this product, read all warnings and directions on the label.