

QUICKCABLE

Material Safety Data Sheet (MSDS)

Description: Protective Washers

Part Number: 6621,6622,6623, 6626,6628

SECTION I CONTACT INFORMATION

Date: June 2010

Quick Cable Corporation
3700 Quick Cable Drive, Franksville, WI 53126
Telephone: 1-800-558-8667

Emergency Telephone: INFOTRAC 1-800-535-5053

Quick Cable Product I.D.: 6621 R&B, 6622 R&B, 6623 R & B
6626 B, 6628 B

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components Specific Chemical Identity (Common Name(s))	CAS #	OSHA-PEL	ACGIH-TLV	Percent
Lube oil- 500 SUS	#64742-52-5	5mg/m3 (mist)	5 mg/m3	70%
Inhibited Paraffinic Oil*	mixture	5mg/ m3 (mist)	5 mg/ m3	30%

*Additional elements may be present in trace amounts (>0.5%)

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor: Amber liquid; if dye added, dark red; typical oil odor
Solubility in Water: Not soluble in water, but soluble in most organic solvents
Boiling Point: N/A
Evaporation Rate (Butyl Acetate=1): N/A

Specific Gravity (H2O=1): 0.911
Vapor Density (AIR=1): N/A
Vapor Pressure (mm Hg): N/A
% Volatile: <1 (0.08 lbs./gal. VOC)

Melting Point: N/A

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): >350°F
Extinguishing Media: Carbon dioxide, foam, dry chemicals
Unusual Fire and Explosion Hazards: Treat as oil fire

Flammable Limits: N/A
Method: COC

SECTION V REACTIVITY DATA

Stability: Stable
Incompatibility (Materials to avoid): Strong oxidizers
Hazardous Decomposition of By-products: Thermal-carbon monoxide

SECTION VI HEALTH HAZARD DATA

Route(s) of Entry: Inhalation and skin. Avoid eye contact
Carcinogenicity: OSHA: No IRAC: No NTP: No
Signs and Symptoms of Exposure: *Inhalation:* Heavy mist concentration may cause breathing difficulties. *Skin and Eyes:* May cause irritation.

Medical Conditions Generally Aggravated by Exposure: N/A

Chemical listed as Carcinogen or Potential Carcinogen: N/A

Emergency and First Aid Procedures:

Inhalation: Remove to fresh air

Ingestion: Do not induce vomiting. Contact medical attention

Eyes: Flush with large amounts of water

Skin: Remove contaminated clothing and wash with soap and water

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Area should be ventilated. Absorbent should be used to pick up excess materials.

Waste Disposal Method: Dispose of any collected material in accordance with local, state or applicable federal regulations.

Precautions to be Taken in Handling and Storing: Store in a cool, dry area.

Other Precautions: N/A

SECTION VIII CONTROL MEASURES

Respiratory Protection (Specific Type): Use NIOSH/MSHA compliant respirators or self contained breathing apparatus above exposure limits.

Ventilation: Adequate to prevent accumulation of vapors.

Protective Clothing: Wear chemically protective gloves, aprons and boots if splashing occurs.

Eye and Face Protection: Safety glasses, face shield if splashing occurs.

Work Hygienic Practices: Good personal hygiene and work practices are recommended.

SECTION IX OTHER REGULATORY INFORMATION

NFPA Hazard Rating	NFPA	HMIS
Health (Blue)	1	1
Flammability (Red)	1	1
Reactivity (Yellow)	0	0

SARA Title III: Section 311/312: N/A **Section 313:** None

Extremely Hazardous Substance: No

California Prop 65: No

This information is accurate to the best of Quick Cable Corporation's knowledge or obtained from sources believed by Quick Cable to be accurate. Before using this product, read all warnings and directions on the label.