



Safety Data Sheet

1. IDENTIFICATION

Product Identifier

Battery protective spray

Other means of identification

Battery terminal protection spray
Battery terminal protector

Product Code

120141

Recommended use of the chemical and restrictions on use

Recommended for commercial/industrial use

Not recommended for household use

Details of the supplier of the safety data sheet

Quick Cable Corporation
3700 Quick Drive
Franksville, WI 53126-0509
www.quickcable.com

Emergency Telephone Number (24 hr)

INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification	Category
Flammable aerosols	1
Gases under pressure	Liquefied gas
Skin corrosion/irritation	2
Carcinogenicity	2
Reproductive toxicity (fertility)	2
Specific target organ toxicity, single exposure	3 narcotic effects
Aspiration hazard	1
Hazardous to the aquatic environment, acute hazard	1
Hazardous to the aquatic environment, long term hazard	1

OSHA defined hazards: Not classified

GHS Label Elements



SIGNAL WORD: Danger

Hazard Statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention: obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces. Do not smoke. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized.

Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Avoid breathing gas. Wear protective gloves/protective clothing, eye protection, face protection. Wash hands thoroughly after handling. Avoid release to the environment.

Response: if swallowed, immediately call a poison center or doctor. Do NOT induce vomiting.

If on skin: Wash with plenty of soap and water. If skin irritation occurs, get medical attention. Take off contaminated clothing and wash before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If exposed or concerned, get medical attention. Collect spillage

Storage: Store in a well ventilated place. Store locked up> Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Exposure to high temperature may cause can to burst.

Disposal: Dispose of contents/container in accordance with local, regional, national, international regulations.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information: 55.54% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 52.75% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS#	Weight %*
n-Hexane	110-54-3	15-25
Petrolatum	8009-03-8	10-15
Naphtha	64742-88-7	5-10
Solvent distillates	64741-88-4	2-5
Xylene	1330-20-7	1-3
Ethylbenzene	100-41-4	<1
Butane	106-97-8	16-24
Propane	74-98-6	22-34

Specific chemical identity and/or percentage of composition have been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do Not induce vomiting. If vomiting occurs, keep head low so that stomach and content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.

Most important symptoms/effects, acute and delayed: Vapors have narcotic effect and may cause headache, fatigue, dizziness, and nausea. May cause drowsiness or dizziness. May cause redness and pain.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information: If exposed or concerned, get medical advice/attention. Ensure that medical personnel are aware of the Material(s) involved and take precautions to protect themselves.

5. FIRE-FIGHTING MEASURES

Extinguishing media: water fog. Carbon dioxide (CO₂). Dry chemical powder. Carbon dioxide, sand, or earth may be used for small fires only.

Unsuitable Extinguishing Media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions: In case of fire, stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

General fire hazards: Extremely flammable aerosol.

6. ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Avoid breathing gas. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand, or earth and place into containers.

Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13.

Environmental precautions: Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses, or onto the ground. Use appropriate containment to avoid environmental contamination.

7. HANDLING AND STORAGE

Precautions for safe handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations.

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy and while nursing. Avoid prolonged exposure. Avoid contact with clothing. Use only in well ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink, or smoke. Wash hands thoroughly after handling. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

Aerosol level – 3

Conditions for safe storage, including any incompatibilities: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50C/122F. Do not puncture, incinerate, or crush. Do not handle or store near an open flame, heat, or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well ventilated place. Store away from incompatible materials (see section 10).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	CAS#	Type	Value	Form
Solvent distillates	64741-88-4	PEL	5 mg/m ³ ; 500 ppm	Mist
Ethylbenzene	100-41-4	PEL	435 mg/m ³ ; 100 ppm	
n-Hexane	110-54-3	PEL	1800 mg/m ³ ; 500 ppm	
Petrolatum	8009-03-8	PEL	5 mg/m ³	Mist
Xylene	1330-20-7	PEL	435 mg/m ³ ; 100 ppm	
Butane	106-97-8	PEL	800 ppm	
Propane	74-98-6	PEL	1000 ppm	

U.S. ACGIH Threshold Limit Values

Components	CAS#	Type	Value	Form
Solvent distillates	64741-88-4	TWA	5 mg/m ³	Inhalable fraction
Ethylbenzene	100-41-4	TWA	20 ppm	
n-Hexane	110-54-3	TWA	50 ppm	
Petrolatum	8009-03-8	TWA	5 mg/m ³	Inhalable fraction
Xylene	1330-20-7	STEL	150 ppm	
		TWA	100 ppm	
Butane	106-97-8	TWA	800 ppm	
			1900 mg/m ³	

U.S. NIOSH: Pocket Guide to Chemical Hazards

Components	CAS#	Type	Value	Form
Solvent distillates	64741-88-4	STEL	10 mg/m3 300 ppm	Mist
Ethylbenzene	100-41-4	TWA STEL	5 mg/m3 545 mg/m3	Mist
n-Hexane	110-54-3	TWA	180 mg/m3 50 ppm	
Petrolatum	8009-03-8	STEL TWA	10 mg/m3 5 mg/m3	Mist Mist
Butane	106-97-8	TWA	1900 mg/m3 800 ppm	
Propane	74-98-6	TWA	1800 mg/m3 1000 ppm	

Biological Limit Values: ACGIH Biological Exposure Indices

Components	CAS#	Value	Determinant	Specimen	Sampling Time
Ethylbenzene	100-41-4	0.7 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
n-Hexane	110-54-3	0.4 mg/l	2, 5-Hexanedion, without hydrolysis	Urine	*
Xylene	1330-20-7	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* For sampling details please see the source document.

Exposure guidelines

U.S. California OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin

U.S. ACGIH Threshold Limit Values: Skin designation

Xylene (CAS 74-98-6) Can be absorbed through the skin

Appropriate engineering controls: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures; personal protective equipment

Eye/face protection: Wear safety glasses with side shields or goggles.

Skin and hand protection: Wear protective gloves such as polyvinyl chloride (PVC), nitrile, viton rubber (fluor rubber). Wear appropriate chemical resistant clothing.

Respiratory protection: If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards: Wear appropriate thermal protective clothing when necessary.

General hygiene considerations: When using, do not eat, drink, or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Form	Aerosol
Color	Dark red	Odor	Petroleum
Odor threshold	Not available	pH	Not available
Melting point/freezing point	-244.7F (-153.7C) estimated	Boiling point/range	118.4F (48C estimated)
Flash point	< 0 F (< -17.8C) closed cup	Evaporation rate	Fast
Flammability (solid, gas)	Not available	Flammability limit – Lower	1% estimated
Flammability limit – Upper	8% estimated	Vapor pressure	1451.7 hPa estimated
Vapor density	Not available	Relative density	0.73
Solubility (water)	Not available	Partition coefficient (n-octanol/ water)	Not available
Auto-ignition temp	500F (260C) estimated	Decomposition temp	Not available
Viscosity (kinematic)	Not available	Percent volatile	88.8% estimated

10. STABILITY AND REACTIVITY

Reactivity: The product is stable and non-reactive under normal conditions of use, storage, and transport

Chemical stability: Material is stable under normal conditions

Possibility of hazardous reactions: No dangerous reaction known under conditions of normal use

Conditions to Avoid: Avoid temperatures exceeding the flash point. Contact with incompatible materials

Incompatible Materials: Strong acids. Strong oxidizing agents. Halogens

Hazardous Decomposition Products: No hazardous decomposition products are known

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure

Ingestion: May be fatal if swallowed and enters airways

Inhalation: Vapors have a narcotic effect and may cause headache, fatigue, dizziness, and nausea. Prolonged inhalation may be harmful.

Skin contact: Causes skin irritation

Eye contact: Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics: Skin irritation. May cause redness and pain. Symptoms of over-exposure may be headache, dizziness, tiredness, nausea, and vomiting.

Toxicological effects

Acute toxicity: May be fatal if swallowed and enters airways. Narcotic effects

Type	Species	Test Results*
Acute		
<i>Dermal</i>		
LD50	Rabbit	2527 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	36645 ppm, 4 hours, estimated 54 mh/l, 4 hours estimated
<i>Oral</i>		
LD50	Rat	5847 mg/kg estimated
Chronic		
<i>Oral</i>		
LD50	Mouse	83g/kg estimated
Sub-chronic		
<i>Oral</i>		
LD50	Rat	10943 g/kg, 14 days estimate

*Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation: Causes skin irritation

Serious eye damage/eye irritation: Direct contact with eyes may cause temporary irritation.

Respiratory sensitization: Not available

Skin sensitization: This product is not expected to cause skin sensitization

Germ cell mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: Suspected of causing cancer

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4) 2B possibly carcinogenic to humans

Xylene (CAS 1330-20-7) 3 not classifiable as to the carcinogenicity to humans

Reproductive toxicity: Possible reproductive hazard. Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility.

Specific target organ Toxicity – single exposure: Narcotic effects

Specific target organ Toxicity – repeated exposure: Not classified

Aspiration hazard: May be fatal if swallowed and enters airways.

Chronic effects: Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Very toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Component / Test Type	Species	Test Results*
Battery Terminal Protection Spray		
Aquatic		
<i>Acute</i>		
Crustacea EC50	Daphnia	177 mg/l, 48 hrs estimated
Fish LC50	Fish	40625 ppm, 96 hours estimated
Ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea EC50	Water flea (Daphnia magna)	2 mg/l, 48 hours
Fish LC50	Fathead minnow (Pimephales promelas)	12 mg/l, 96 hours
n-Hexane (CAS 110-54-3)		
Aquatic		
Fish LC50	Fathead minnow (Pimephales promelas)	2.1 – 2.9 mg/l, 96 hours
Xylene (CAS 1330-20-7)		
Aquatic		
Fish LC50	Rainbow trout, Donaldson trout (Oncorhynchus mykiss)	9.5 – 19 mg/l, 96 hours

*Estimates for product may be based on additional component data not shown.

Persistence and degradability: No data is available on the degradability of this product.

Bioaccumulative potential: No data available

Partition coefficient n-octanol/water (log Kow)

Xylene 3.15

n-Hexane 3.9

Partition coefficient n-octanol/water (log Kow)

Xylene 3.12 – 3.2

Bioconcentration factor (BCF)

Xylene 15

Mobility in soil: Not data available**Other adverse effects:** No other adverse environmental effects, e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential are expected from this component.**13. DISPOSAL CONSIDERATIONS****Disposal of waste from residues/unused products:** This material and its container must be disposed of as hazardous waste. If discarded, this product is considered an RCRA ignitable waste, D001. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers or water supplies. Do not contaminate ponds, waterways, or ditches with chemical or used container. Dispose of contents/container in accordance with local, regional, national regulations.**Hazardous waste code:** D001; Waste Flammable material with a flash point < 140F**Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.**14. TRANSPORT INFORMATION****DOT**

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard classes:	
Class	2.1
Subsidiary risk	-
Labels	2.1
Packing group	Not applicable
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling
Special provisions	Not available
Packaging exceptions	306
Packaging non-bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, limited quantity
Transport hazard classes:	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable
Environmental hazards	No
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling
Other information:	
Passenger and cargo aircraft	Allowed
Cargo aircraft only	Allowed

IMDG

UN number	UN1950
UN proper shipping name	Aerosols, limited quantity
Transport hazard classes:	
Class	2
Subsidiary risk	-
Packing group	Not applicable
Environmental hazards Marine pollutant	No
EmS	Not available
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling

15. REGULATORY INFORMATION

U.S. Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

TSCA Section 12(b) Export Notification, 40 CFR 707, subpart D: Not regulated

SARA 304 Emergency Release Notification: Not regulated

U.S. OSHA Specifically Regulated Substances, 29 CFR 1910.1001.1050: Not listed

U.S. EPCRA (SARA Title III) Section 313 – Toxic Chemical: Listed Substance

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

CERCLA Hazardous Substance List, 40 CFR 302.4

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

CERCLA Hazardous Substances: Reportable Quantity

Ethylbenzene (CAS 100-41-4) 1000 lbs

Xylene (CAS 1330-20-7) 100 lbs

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention, 40 CFR 68.130: Not regulated

Safe Drinking Water Act (SDWA): Not regulated

Food and Drug Administration (FDA): Not regulated

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Hazard Categories:

Immediate hazard No

Delayed hazard Yes

Fire hazard No

Pressure hazard Yes

Reactivity hazard No

SARA 302 Extremely Hazardous Substance: No

U.S. State regulations

New Jersey Worker and Community Right to Know Act

Ethylbenzene (CAS 100-41-4)

n-Hexane (CAS 110-54-3)

Xylene (CAS 1330-20-7)

Massachusetts RTK Substance List

Xylene (CAS 1330-20-7)

Pennsylvania Worker and Community Right to Know Law

Ethylbenzene (CAS 100-41-4)

n-Hexane (CAS 110-54-3)

Xylene (CAS 1330-20-7)

Rhode Island RTK

Ethylbenzene (CAS 100-41-4)

n-Hexane (CAS 110-54-3)

Xylene (CAS 1330-20-7)

California Proposition 65: WARNING, This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

California Proposition 65 – CRT: Listed date/carcinogenic substance

Benzene (CAS 71-43-2) listed February 27, 1987

C.I. Solvent Yellow 14 (CAS 842-07-9) listed May 15, 1998

C.I. Solvent Yellow 3 (CAS 97-56-3) listed July 1, 1987

Ethylbenzene (CAS 100-41-4) listed June 11, 2004

Naphthalene (CAS 91-20-3) listed April 19, 2002

California Proposition 65 – CRT: Listed date/developmental toxin

Benzene (CAS 71-43-2) listed December 26, 1997

Toluene (CAS 108-88-3) Listed January 1, 1991

California Proposition 65 – CRT: Listed date/female reproductive toxin

Toluene (CAS 108-88-3) Listed August 7, 2009

California Proposition 65 – CRT: Listed date/male reproductive toxin

Benzene (CAS 71-43-2) listed December 26, 1997

Volatile Organic Compounds (VOC) regulations

EPA

VOC content, 40 CFR 51.100(s) 86.3%

Consumer products, 40 CFR 59 subpart C Not regulated

State

Consumer products Not regulated

International Inventories

Countries/Regions	Inventory name	On inventory Yes/No*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
US & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

* A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. OTHER INFORMATION

Hazardous Materials Information Systems HMIS ratings

HEALTH	*2
FLAMMABILITY	4
REACTIVITY	1
PERSONAL PROTECTION	B

National Fire Protection Association NFPA ratings



Blue = Health

Red = Flammability

Yellow = Instability

Issue Date: 02/20/2015

Revision Date: 03/30/2015

Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.