

Quick Cable Reserves The Right to Alter Product Types, Their Technical Data, Dimensions, Style And Accessories Without Prior Notification.

**I.D.Sized For 250MCM
[126mm²] Stranded Cable
7/8" [22.2mm] Min Depth**

**27/32" O.D. [21.2mm]
(May Vary Due
To Shrinkage)**

**Bolt Hole Sized
For 5/16" [M8] Bolt**

47/64" [18.5mm]

2-3/32" [53.2mm]

**Sized For Neg. Post
Per SAE J537**

1-19/32" [40.5mm]

**Crimp
Information**

**Polarity
Stamp**

Property of QUICKCABLE® 3700 Quick Drive Franksville, WI 53126 U.S.A. www.quickcable.com		TITLE Right Elbow, Neg. 250MCM [126mm²]	
		PART # 4160N	
Confidential and Proprietary Information			
Material & Treatment High Conductivity Copper Alloy Tin Plated		Drawing # 4160N-INFO	REV C
		Sheet 1 Of 1	

					Drawn By	Date	Checked By	Scale
					Jim H	12-21-05	Mike E	None
					Tolerances, unless otherwise noted			
					Dimensions are reference only			
C	07-09-12	2450	JMM	Redrawn; printing info updated				
Rev	Date	ECN#	By	Description				